ROUTING RECORD

DATE	FROM	TO	ACTION ()
4-18-08	10 GA	6R6	Prescrean W
4-23-08	GRA		I Accept C/C
2-12-09			PO RECOM. C/C for ECF
4-14-09	Gast	ADOD!	Par-PO 49 -110
5-26-09	ADOIL	CADI	1010 Approved (TV)
			11
			<u> </u>

REFERENCE TO OTHER APCD RECORDS INCLUDING VARIANCES
496824

G 2964

APPL # 480911 I. D. # 29110

ORANGE COUNTY SANITATION DISTRICT 22212 BROOKHURST ST HUNTINGTON BEACH INTERNAL COMBUSTION ENGINE

Date. 04/02/08

Ident-3



South Coast Air Quality Management District

# Form 400-A Application For Permit To Construct and Permit To Operate

Mail Application To: P.O. Box 4944 Diamond Bar, CA 91765

> Tel: (909) 396-3385 www.aqmd.gov

Section A: Operator Information		Tool Service Control of the Control
Business Name of Operator To Appea  Orongo County Conitation Dis-		Approximation of the discourse of the di
Orange County Sanitation Dis  2. Valid AQMD Facility ID (Available on I	elita mandanakanakan orang mengang mengangkan dan sebesah sebe	ame (only If different from Business Name of Operator):
issued by AQMD): 029110	J. Officer a Dasiness N	ane (only it different from business waite of Operator).
Section B: Equipment Location	The state of the s	Section C: Permit Mailing Address
Equipment Location Address:  Engaginment appropriate of various location	ons in AQMD's jurisdiction, provide address of initial site	5. Permit and Correspondence Information:
To equipment operated at various located	ons in Action s jurisdiction, provide address of mittal site	Check here if same as equipment location address
22212 Brookhurst Street		10844 Ellis Avenue
Street Address		Street Address
Huntington Beach	ca, 92646 _ 8406	Fountain Valley CA 92708 - 7018
City	State Zip Code	City State Zip Code
County: C Los Angeles Orange	San Bernardino Riverside	
Contact Name: Vlad Kogan	**************************************	Contact Name: Vlad Kogan
Contact Title: Senior Scientist	Phone: (714) 593-7085	Contact Title: Senior Scientist Phone: (714) 593-7085
Fax: (714) 962-8379 E-Mai	il: vkogan@ocsd.com	Fax: (714) 962-8379 E-Mail: vkogan@ocsd.com
Section D: Application Type T	The facility is in ○RECLAIM ○ Ti	tle V C RECLAIM & Title V Program (please check if applicable)
6. Reason for Submitting Application (Se	elect only ONE):	7. Estimated Start Date of Operation/Construction (MM/DD/YYYY):
New Construction (Permit to	Permitted Equipment Altered/ Modified Without	Dut 8. Description of Equipment:
Construct)	Permit Approval*	Internal Combustion Engine (CG3-HB), Cooper Bessemer, Model
C Equipment Operating Without A Permit or Expired Permit*	Proposed Alteration/Modification to Permitted Equipment	No. LSVB-16-SGC, 4166 HP, Natural Gas and/or Digester Gas Fired, Driving a 3000 KW Electric Generator
Administrative Change	Change of Condition For Permit To Operate	
Constructed or Operational	Change of Condition For Permit To Construc	9. Is this equipment portable AND will it be operated at different locations within AQMD's jurisdiction?
Title V Application (Initial, Revisions, Modifications, etc.)	C Change of Location—Moving to New Site	For Identical equipment, how many additional applications are being submitted with this application? (Form 400-A required for each)
Compliance Plan	Existing Or Previous Permit/Application Number:	4
Facility Permit Amendment	provide a existing Permit/ Application Number)	11. Are you a Small Business as per AQMD's Rule 102 definition? (10 employees or less and total gross receipts are \$500,000 or less,
	A/N 414655	or a not-for-profit training center?)
Registration/Certification		12. Has a Notice of Violation (NOV) or a Notice To Comply (NC) been issued for this equipment?
O Streamlined Standard Permit		● No ○ Yes If yes, provide NOV/NC #:
A Higher Permit Processing Fee applies to the Section E: Facility Business Info	ose items with an asterisk (Rule 301 (c) (1) (D)	TO CHES II yes, provide ACAMO #.
13. What type of business is being conduc		14. What is your businesses primary NAICS Code
Municipal Wastewater Treatme	nt	(North American Industrial Classification System)?
15. Are there other facilities in the SCAQM0 by the same operator?	D jurisdiction operated O No • Yes	16. Are there any schools (K-12) within a 1000-ft. radius of the equipment physical location?  • No • Yes
	Fe I hereby certify that all information contained herein	and information submitted with this application is true and correct.
17. Signature of Responsible Official:	18. Title:	Check List
Willer M.	Manager, ECRA	Form(s):signed and dated by authorized official  Supplemental Equipment Form (400-E-XX or 400-E-GEN)
19. Print Name:	20. Date:	CEQA Form (400-CEQA) attached
Mike D. Moore	3/24/6	Payment for permit processing fee attached
WIRES D. WOORS	monare manare manare man a manare	Your application will be rejected if any of the above items are missing
USE ONLY APPLICATION/TRACK	1 BED 056	057   \$1367.36 4 04   04   04
ENG. (A) R ENG. A  DATE U173 168 GCR DATE  South Charl Air Quality Management District E	R CLASS ASSIGNMENT    Jill IV Unit Engine	# 1 000 399023 \$ 8204 15

CIT 69016

3 15

Ident. Eg.

08 ABR -2 P257

South Coast Air Quality Management District

### Form 400-CEQA

### California Environmental Quality Act (CEQA) Applicability

Mail Application To: P.O. Box 4944 Diamond Bar, CA 91765

Tel: (909) 396-3385

www.aqmd.gov

The SCAQMD is required by state law, the California Environmental Quality Act (CEQA), to review discretionary permit project applications for potential air quality and other environmental impacts. This form is a screening tool to assist the SCAQMD in clarifying whether or not the project has the potential to generate significant adverse environmental impacts that might require preparation of a CEQA document [CEQA Guidelines §15060(a)].<sup>2</sup> Refer to the attached instructions for guidance in completing this form.<sup>3</sup> For each Form 400-A application, also complete and submit one Form 400-CEQA. If submitting multiple Form 400-A applications for the same project at the same time, only one 400-CEQA form is necessary for the entire project. If you need assistance completing this form, contact Lori Inga at (909) 396-3109.

	ILITY-INF			in representation of trade of Frenches (1966) by	ng midawana			
			r to Appear on the Permit:	Facility ID (6-Digit):				
Orai	nge Cou	nty Sani	lation District		029110			
Projec	t Descripti	on:						
Cha	nge of co	andition	for Permit to Construct to allow permitted internal combustion	on anaines to comply with the	roquiromente			
of R	ule 1110	.2 - Emi	ssions from Gaseous- and Liquid-Fueled Engines as amen	ded on February 1, 2008.	requirements			
WALL SALES STATE OF THE SALES	ner en miliona en limbouer common d	en montro de miner e a designa de descria		A - han a l'hadration a sange, y considération e quantitation and agreement strangers comme constituent and a				
REVI	EW FOR	EXEMP	TION FROM FURTHER CEQA ACTION		E CARLO SERVICE			
	"Yes" or "N							
	Yes	No	Is this application for:					
A.	0	•	A CEQA and/or NEPA document previously or currently prepared permit cannot be issued until a Final CEQA document and Notice of Determina		roject? If yes, a			
В.	0	•	A request for a change of permittee only (without equipment mod	fifications)?				
C.	0	•	Equipment certification or equipment registration (qualifies for Rule	222)?				
Ð.	0	•	A functionally identical permit unit replacement with no increase in rating or emissions?					
E.	0	A change of daily VOC permit limit to a monthly VOC permit limit?						
F.	0	0	Equipment damaged as a result of a disaster during state of emergency?					
G.	G. A Title V (i.e., Regulation XXX) permit renewal (without equipment modifications)?							
Н.	H. O							
1. O The conversion of an existing permit into an initial Title V permit?								
If "Yes" date thi		l for any qu	estion above, your application does not require additional evaluation for CEQA ap	oplicability. Skip to page 2, "SIGNATURI	ES" and sign and			
REVIE	WOFIN	PACTS	WHICH MAY TRIGGER CEQA					
	te Sections to this form		cking "Yes" or "No" as applicable. To avoid delays in processing your application	n(s), explain all "Yes" responses on a sep	arate sheet and			
	Yes	No	Section I – General	an and had superior in the				
1.			Has this project generated any known public controversy regarding	ng potential adverse impacts that	may be			
	0	•	generated by the project?					
			Controversy may be construed as concerns raised by local groups at public me newspapers or other periodical publications, local news programs, environment		negative articles in			
2.	0	•	Is this project part of a larger project?					
			Section II - Air Quality					
3.	0	0	Will there be any demolition, excavating, and/or grading construc 20,000 square feet?	tion activities that encompass an	area exceeding			
4.	0	•	Does this project include the open outdoor storage of dry bulk so include a plot plan with the application package.	lid materials that could generate o	dust? If Yes,			

<sup>&</sup>lt;sup>1</sup> A "project" means the whole of an action which has a potential for resulting in physical change to the environment, including construction activities, clearing or grading of land, improvements to existing structures, and activities or equipment involving the issuance of a permit. For example, a project might include installation of a new, or modification of an existing internal combustion engine, dry-cleaning facility, boiler, gas turbine, spray coating booth, solvent cleaning tank, etc.

<sup>2</sup> To download the CEQA guidelines, visit <a href="http://ceres.ca.gov/eny\_law/state.html">http://ceres.ca.gov/eny\_law/state.html</a>.

<sup>&</sup>lt;sup>3</sup> To download this form and the instructions, visit <a href="http://www.aqmd.gov/ceqa">http://www.aqmd.gov/ceqa</a> or <a href="http://www.aqmd.gov/permit">http://www.aqmd.gov/permit</a>

	Yes	No					
5.	0	•	Would this project result in noticeable off-site odors from activities that may not be subject to SCAQMD permit requirements?  For example, compost materials or other types of greenwaste (i.e., lawn climpings, tree trimmings, etc.) have the notential to generate odor.				
			For example, compost materials or other types of greenwaste (i.e., lawn clippings, tree trimmings, etc.) have the potential to generate odor complaints subject to Rule 402 – Nuisance.  Does this project cause an increase of emissions from marine vessels, trains and/or airplanes?				
6.	0	•	Does this project cause an increase of emissions from marine vessels, trains and/or airplanes?				
7.	0	•	Will the proposed project increase the QUAI by mobile vehicle to or from the site by grea attached Table 1?4				
			Section III - Water Resources			enokana etakan pering	ené apolicárez nerájbon c
8.			Will the project increase demand for water a	t the fac	ility by more tha	n 5,000,000 gallons per da	y?
	0	•	The following examples identify some, but not all, typ- generate steam; 2) projects that use water as part of production process; 4) projects that require new or ex exceeds the capacity of the local water purveyor to su existing water supply facilities.	the air pol pansion o	ution control equipa f existing sewage to	ment; 3) projects that require wa reatment facilities; 5) projects wi	ater as part of the here water demand
9.			Will the project require construction of new	water co	nveyance infras	tructure?	
	0	•	Examples of such projects are when water demands or require new or modified sewage treatment facilities	exceed the such that	e capacity of the loc the project require	cal water purveyor to supply suff s new water lines, sewage lines	ficient water for the project, , sewage hook-ups, etc.
			Section IV – Transportation/Circulation			antare e emigr	
10.			Will the project result in (Check all that apply):				
	0	•	a. the need for more than 350 new employee	s?	·		
	0	•	b. an increase in heavy-duty transport truck day?	traffic to	and/or from th	e facility by more than 350	truck round-trips per
	0	•	c. increase customer traffic by more than 70	0 visits	per day?	•	
			Section V - Noise				(12)
11.	C	•	Will the project include equipment that will g	enerate	noise GREATER	R THAN 90 decibels (dB) at	the property line?
			Section VI - Public Services				
12.	1040		Will the project create a permanent need for that apply):	new or a	dditional public	services in any of the foll	owing areas (Check all
	0	•	a. Solid waste disposal? Check "No" if the projected potential amount of wastes generated by the project is less than five tons per day.				
	0	b. Hazardous waste disposal? Check "No" if the projected potential amount of hazardous wastes generated by the project is less than 42 cubic yards per day (or equivalent in pounds).					
**REMINDER: For each "Yes" checked in the sections above, attach all pertinent information including but not limited to estimated quantities, volumes, weights, etc.							
SIGN	ATURES			1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			
BEST	OF MY KNO	WLEDGE.	LL INFORMATION CONTAINED HEREIN AND INFOR: I UNDERSTAND THAT THIS FORM IS A SCREENING IN DETERMINING CEQA APPLICABILITY.				
SIGNA	TURE OF R	ESPONSIE	ILE OFFICIAL OF FIRM:		TITLE OF RESPO	ONSIBLE OFFICIAL OF FIRM:	
W	llle	U/	1. Move		Manager, E	CRA	
			ESPONSIBLE OFFICIAL OF FIRM:	RESPON	ISIBLE OFFICIAL'	S TELEPHONE NUMBER: 🔑	DATE Signed:
***************************************	D. Moore	-		W 2 CAMP LIBRARY STATE	5937-450		3/26/08
SIGNA	TURE OF P	REPARER	, IF PREPARED BY PERSON OTHER THAN RESPONSIBLE OFFI	CIAL OF FIF	М:	TITLE OF PREPARER:	
			O KOBAN			Senior Scientist	
l	OR PRINT N Kodan	AME OF P	REPARER:		PREPARER'S TE	ELEPHONE NUMBER:	DATE Signed:
1/13/1	n OOBD				1/14/3944/-	11(3.1	11111111

THIS CONCLUDES FORM 400-CEQA. INCLUDE THIS FORM AND THE ATTACHMENTS WITH FORM 400-A.

<sup>&</sup>lt;sup>4</sup> Table 1 – Regulated Substances List and Threshold Quantities for Accidental Release Prevention can be found in the Instructions for Form 400-CEQA.

Table 1 Plant 2 Digester Gas Production, Fuel Consumption and Electricity Generation for 2007

		Diges	Digester Gas Usage	sade	Nati	Natural Gas Usano	Sarre					
			High			High			7 7 7 7 7			
-						ກ			Lercent		•	lotai
	Digester Gas		Heating	Heating		Heating	Heating	Total Fuel	Natural	Engine	Steam	Electricity
	Production	Quantity	Value	Value	Quantity	Value	Value	Usage	Gas	Output	Turbine	Generated
	(kscf)	(kscf)	(Btu/ft³)	(therms)	(kscf)	(Btu/ft³)	(therms)	(therms)	Usage	(kwh)	(kwh)	(kwh)
January	83,200	76,462	626	478,653	9,238	1,020	94,231	572,884	16.45%	6,370,264	205,736	6,576,000
February	74,100	68,047	622	423,250	9,953	1,027	102,219	525,469	19.45%	5,990,381	185,619	6,176,000
March	80,500	75,245	625	470,283	9,534	1,018	97,058	567,341	17.11%	5,530,447	197,553	5,728,000
April	73,200	71,574	625	447,336	10,591	1,018	107,813	555,149	19.42%	4,590,124	177,876	4,768,000
May	74,600	71,972	621	446,947	5,213	1,020	53,169	500,116	10.63%	4,615,155	200,845	4,816,000
June	71,600	70,639	624	440,785	16,881	1,019	172,019	612,805	28.07%	4,709,525	218,475	4,928,000
July	72,300	72,372	634	458,840	17,345	1,020	176,922	635,762	27.83%	5,263,663	176,337	5,440,000
August	73,700	73,964	634	468,929	17,274	1,018	175,844	644,773	27.27%	5,395,018	236,982	5,632,000
September	65,200	65,705	627	411,970	18,088	1,016	183,769	595,739	30.85%	5,035,483	148,517	5,184,000
October	68,400	68,565	631	432,645	15,401	1,016	156,471	589,116	26.56%	4,944,000	0	4,944,000
November	66,600	68,012	634	431,196	13,186	1,021	134,629	565,825	23.79%	4,704,000	0	4,704,000
December	70,300	68,995	630	434,671	13,675	1,019	139,345	574,016	24.28%	4,832,000	0	4,832,000
Average	72,808	70,963	628	445,459	13,032	1,019	132,791	578,250	22.64%	5,165,005	145,662	5,310,667
TOTAL	873,700	851,552		5,345,505	156,379		1,593,489	6,938,995		61,980,060 1,747,940	1,747,940	63,728,000

kscf = 1000 standard cubic feet

Table 2
Plant 2 Power Demand for 2007

Conditions	Total OCSD Flow (MGD)	Energy Demand (MW)	Numbers of Engines in Operation	Monthly CGS Output (MW)
Dry Weather	240-320	7.8-8.5	3 @ 70-80% Load, 70-80% Di-Gas	7.1-8.8
Wet Weather (Heavy Rain/Melting Snow)	320-400	10.0-12.0	4 @ 90-100% Load, 60% Di-Gas	9.3-10.7
Peak Wet Weather (Heavy Rainstorm)	400-500	13.0-16.0	5 @ 100% Load, 50% Di-Gas	12.0-15.0

MGD = Million Gallons per Day MW = Megawatt

ORANGE COUNTY 10844 Ellis Avenue, P.O. Box 8127
SANITATION DISTRICT Fountain Valley, CA 92728-8127
(714) 962-2411

**VENDOR NO. 15843** 

DATE: 03/05/08 CHECK NO. 1000099023

VENDOR NAME SOUTH COAST AIR QUALITY MGT RE

INVOICE NO.	INVOICE DATE	DESCRIPTION	NC	GROSS AMOUNT	DISC ADJ.	PAYMENT AMOUN
ERMIT FEES	02/20/08			8,204.15		8,204.15
				en e		· .
						in the second second

### FEE DATA - SUMMARY SHEET

Application No

480911



IRS/SS No:

Previous Application No:

414655

Previous Permit No: F9602

Company Name:

ORANGE COUNTY SANITATION DISTRICT

Facility ID:

29110

Equipment Street:

22212 BROOKHURSTST, HUNTINGTON BEACH CA 92646

Equipment Desc :

ICE (>500 HP) NAT & DIGESTER GAS

Equipment Type:

BASIC

Fee Charged by: **B-CAT** 

B-CAT NO.

056057

C-CAT NO:

00

Fee Schedule: D

Facility Zone

18

Deemed Compl. Date:

4/23/2008

Public Notice: NO

Evaluation Type :

CHANGE OF CONDITIONS, (PO)

Higher Fees for Failing

Small Business:

Disposition

E.I.R

Approve PO, Recommended by Engineer

to Obtain a Permit:

Identical Permit Unit:

Lead Appl. No :

480908

 \$0.00
 Filing Fee Paid:
 \$0.00

 \$0.00
 Permit Processing Fee Paid:
 \$1,367.36

Health Risk Assessment

Permit Processing Fee Paid:

Permit Processing Fee
Calculated\*:

\$1,367.36

Significant Project

Air quality Analysis

.

0.00

Permit Processing Fee Adjustment:

\$0.00

Expedited Processing
Source Test Review

Hours:

0.00

\$0.00

\$0.00

\$0.00

\$0.00

\$0.00

Time & Material

Hours:

0.00

\$0.00

Additional Charge:

Total Additional Fee:

\$0.00

COMMENTS: CHANGE OF CONDITION FOR EMISSION CORRECTION FACTOR (ECF), RULE 1110.2

RECOMMENDED BY: GAURANG RAWAL	DATE: 02/10/2009
REVIEWED BY: CO	DATE: 5/26/69

### SCAQMD PERMIT PROCESSING SYSTEM (PPS)

### **AEIS DATA SHEET**

Company Name: ORANGE COUNTY SANITATION DISTRICT

Facility ID: 29110

Equipment Address: 22212 BROOKHURST ST

**HUNTINGTON BEACH CA 92646** 

Application Number: 480911

Equipment B-Cat: 056057

Estimated Completion Date: 02/11/09

Equipment C-Cat:

Equipment Type: Basic

Equipment Description: I C E (>500 HP) NAT & DIGESTER GAS

	Emis	sions	
Emittants	R1 LB/HR	R2 LB/HR	
со	27.60	27.60	
NOX	8.52	8.52	
PM10	0.75	0.75	
ROG	3.87	3.87	
sox ·	0.87	0.87	

Applicable Rules

1110.2 02/01/2008 Emissions from Gaseous-and Liquid-fueled Engines

401

11/09/2001

Visible Emissions

402

05/07/1976

Nuisance

•	Mon	Tue	Wed	Thu	Fri -	Sat	Sun
Daily Start Times:	00:00	00:00	00:00	00:00	00:00	00:00	00:00
Daily Stop Times :	24:00	24:00	24:00	24:00	24:00	24:00	24:00

User's Initials: GR01

Date: 02/11/09

Supervisor's Name:

CAT

Review Date : 5 /26/09

### NSR DATA SUMMARY SHEET

Application No:

480911

Application Type:

Change of Conditions

Application Status:

PENDAPPRV

Previous Apps, Dev, Permit #: 414655, 0 - ICE-PPS, NONE

Company Name:

ORANGE COUNTY SANITATION DISTRICT

Company ID:

29110

Address:

22212 BROOKHURST ST, HUNTINGTON BEACH, CA

RECLAIM: アラモCLAIM Zone: NO

. .. Basin:

01

SC

Zone: Title V:

18 YES

0 - ICE-PPS

Device ID: Estimated Completion Date: 12-30-2008

Heat Input Capacity:

Million BTU/hr 33

Priority Reserve:

NONE - No Priority Access Requested

Recommended Disposition: 31 - PERMIT TO OPERATE GRANTED

PR Expiration:

School Within 1000 Feet: NO Operating Weeks Per Year: 52 Operating Days Per Week: 7

Monday Operating Hours: 00:00 to 24:00 Tuesday Operating Hours: 00:00 to 24:00 Wednesday Operating Hours: 00:00 to 24:00 ursday Operating Hours: 00:00 to 24:00 Friday Operating Hours: 00:00 to 24:00 Saturday Operating Hours: 00:00 to 24:00 Sunday Operating Hours: 00:00 to 24:00

Emittant:

CO

BACT:

Cost Effectiveness:

NO

Source Type:

**MAJOR** 

Emis Increase: Modeling:

0 N/A

Public Notice:

N/A

CONTROLLED EMISSION

Max Hourly:

27.6 lbs/hr

Max Daily:

662.4 lbs/day

**UNCONTROLLED EMISSION** Max Hourly:

27.6 lbs/hr

Max Daily:

662.4 lbs/day

**CURRENT EMISSION** 

BACT 30 days Avg:

672 lbs/day

Annual Emission:

241113.6 lbs/yr

District Exemption:

None

Emittant:

NOX

BACT:

Cost Effectiveness:

NO

Source Type:

**MAJOR** 

Emis Increase:

0

Modeling:

N/A

Public Notice:

N/A

CONTROLLED EMISSION

Max Hourly:

8.52 lbs/hr

Max Daily:

204.48 lbs/day

UNCONTROLLED EMISSION

Max Hourly:

8.52 lbs/hr

Max Daily:

204.48 lbs/day

**CURRENT EMISSION** 

BACT 30 days Avg:

207 lbs/day

Annual Emission: District Exemption:

74430.72 lbs/yr None

Emittant:

PM10

BACT:

Cost Effectiveness:

NO

Source Type: Emis Increase: **MINOR** 

Modeling:

0

N/A

Public Notice:

N/A CONTROLLED EMISSION

Max Hourly:

0.75 lbs/hr

Max Daily:

18 lbs/day

UNCONTROLLED EMISSION

Max Hourly:

0.75 lbs/hr

Max Daily:

18 lbs/day

**CURRENT EMISSION** 

BACT 30 days Avg:

18 lbs/day

Annual Emission:

6552 lbs/yr

District Exemption:

None

ROG Emittant: BACT: Cost Effectiveness: NO Source Type: **MINOR** Emis Increase: 0 Modeling: N/A Public Notice: N/A CONTROLLED EMISSION Max Hourly: 3.87 lbs/hr Max Daily: 92.88 lbs/day **UNCONTROLLED EMISSION** Max Hourly: 3.87 lbs/hr Max Daily: 92.88 lbs/day **CURRENT EMISSION** BACT 30 days Avg: 94 lbs/day Annual Emission: 33808.32 lbs/yr District Exemption: None SOX Emittant: BACT: Cost Effectiveness: NO MINOR Source Type: Emis Increase: 0 Modeling: N/A Public Notice: N/A CONTROLLED EMISSION Max Hourly: 0.87 lbs/hr Max Daily: 20.88 lbs/day **UNCONTROLLED EMISSION** Max Hourly: 0.87 lbs/hr Max Daily: 20.88 lbs/day **CURRENT EMISSION** BACT 30 days Avg: 21 lbs/day Annual Emission: 7600.32 lbs/yr District Exemption: None SUPERVISOR'S REVIEW DATE: 5/26/09 SUPERVISOR'S APPROVAL:

Processed By: gaurangr 2/10/2009 11:46:53 AM



### SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT 21865 Copley Drive, Diamond Bar, CA 91765

Section D Page 55 Facility LD.#: 029110 Revision #: 01

Date: May 28, 2009

## FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

### PERMIT TO OPERATE

Permit No. G2964 A/N 480911

### **Equipment Description:**

RESOURCE RECOVERY SYSTEM NO. 3 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG3-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### Conditions:

- OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW. \*\*[RULE 204]
- 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES. [RULE 204]
- THIS EQUIPMENT SHALL BE OPERATED BY PERSONNEL PROPERLY TRAINED IN ITS OPERATION. 3. [RULE 204]
- 4. THIS ENGINE SHALL HAVE AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER TO DETERMINE THE ENGINE ELAPSED OPERATING TIME FOR EACH FUEL BLEND BURNED. [RULE 1110.2]
- A FLOW INDICATING AND RECORDING DEVICE SHALL BE INSTALLED IN THE FUEL GAS, OR FUEL BLEND, SUPPLY LINE TO THE ENGINE TO MEASURE AND RECORD THE QUANTITY OF EACH FUEL GAS (IN SCFM) BURNED. [RULE 204]
- 6. SAMPLING PORT SHALL BE INSTALLED FOR THE INLET GAS LINE TO THE ENGINE TO ALLOW THE COLLECTION OF A FUEL GAS OR FUEL BLEND SAMPLES. [RULE 204]
- 7. MONTHLY READINGS OF THE BTU CONTENT OF FUEL GAS (BTU/SCF) AT THE COMBINED INLET TO THE CGS ENGINES SHALL BE TAKEN USING AN INSTRUMENT APPROVED BY THE SCAQMD. ALL RESULTS SHALL BE RECORDED. [RULE 204]
- 8. ALL RECORDING DEVICES SHALL BE SYNCHRONIZED WITH RESPECT TO THE TIME OF THE DAY. [RULE 204]

## SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT 21865 Copley Drive, Diamond Bar, CA 91765

Section D Page 56
Facility I.D.#: 029110
Revision #: 01
Date: May 28, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

- 9. THE TOTAL HEAT INPUT OF GASEOUS FUEL, OR FUEL BLEND, BURNED IN THIS ENGINE SHALL NOT EXCEED 33 MM BTU PER HOUR. A LOG SHALL BE KEPT INDICATING THE TOTAL HEATING VALUE OF FUEL GAS, OR FUEL BLEND, BURNED IN THIS ENGINE BASED ON THE RECORDED FLOW RATE (SCFM) AND THE LATEST MONTHLY BTU CONTENT READING. [RULE 1303 (b) (1) AND 1303 (b) (2)-MODELING AND EMISSIONS OFFSET]
- 10. THIS EQUIPMENT SHALL BE OPERATED IN COMPLIANCE WITH RULES 218, 431.1 AND 1110.2. [RULE 218, 431.1 AND 1110.2]
- 11. THIS EQUIPMENT SHALL BE OPERATED IN SUCH A MANNER THAT THE FOLLOWING EMISSION RATES ARE NOT EXCEEDED.

AIR CONTAMINANT

. ---

CARBON MONOXIDE 600 PPMV AT 15% O2
PARTICULATES (PM10) 0.0058 GRAINS/ DSCF
ROG OR TNMHC (AS CARBON) 93 PPMV AT 15% O2
[RULE 1303 (a) (1), 1303(b) (1) AND 1303 (b) (2)-BACT, MODELING AND EMISSIONS OFFSET]

12. THE COMBINED EMISSIONS FROM THE THREE (3) CGS ENGINES, USING CALENDAR MONTHLY EMISSIONS DIVIDED BY 30, SHALL NOT EXCEED THE FOLLOWING:

AIR CONTAMINANT	LBS/DAY
CARBON MONOXIDE	2,644
NITROGEN OXIDES (AS NO2)	828
PARTICULATES (PM10)	72
ROG OR TNMHC (AS CH4)	372
SULFUR DIOXIDE	84
[RULE 1303 (b) (2)-EMISSIONS OFFSET]	

- 13. THE OPERATOR SHALL INSTALL AND MAINTAIN A CONTINUOUS EMISSION MONITORING SYSTEM (CEMS), OR AN ALTERNATIVE SYSTEM, AS APPROVED BY THE EXECUTIVE OFFICER, TO MEASURE THE ENGINE EXHAUST FOR NOx AND O2 CONCENTRATIONS ON A DRY BASIS, EXCEPT DURING SHUTDOWN FOR MAINTENANCE OF THE SYSTEM. IN ADDITION, THE CEMS SHALL CONVERT THE ACTUAL NOx TO MASS EMISSION RATES; AND RECORD THE ACTUAL AND CORRECTED ENGINE NOx CONCENTRATION AT 15% O2 AND MASS EMISSION RATES ON AN HOURLY AND DAILY BASIS.

  [RULE 218, RULE 1110.2]
- 14. THE OPERATOR SHALL CONDUCT PERFORMANCE TESTS ANNUALLY. WRITTEN NOTICE OF THE PERFORMANCE TEST SHALL BE PROVIDED TO THE AQMD AT LEAST 7 DAYS PRIOR TO THE TEST SO THAT AN OBSERVER MAY BE PRESENT. A COMPLETE FINAL REPORT OF THE TEST (LBS/HR, PPMVD AT 15% O2, LBS/MMBTU, ETC.) SHALL BE PROVIDED TO THE AQMD WITHIN 45 DAYS AFTER TESTING. ALL TEST RUNS REQUIRED BY AQMD SHALL BE REPORTED. THE TESTS SHALL INCLUDE BUT NOT BE LIMITED TO, A TEST OF THE FUELS BURNED AND ENGINE EXHAUST FOR:
  - A. TOTAL NON-METHANE HYDROCARBONS (EXHAUST ONLY)
  - B. CARBON MONOXIDE (EXHAUST ONLY)
  - C. TOTAL PARTICULATE MATTER (EXHAUST ONLY).



## SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT 21865 Copley Drive, Diamond Bar, CA 91765

Section D Page 57 Facility I.D.#: 029110 Revision #: 01

Date: May 28, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

- D. OXIDES OF NITROGEN (EXHAUST ONLY).
- E. OXYGEN
- F. FLOW RATE
- G. MOISTURE
- H. TOXIC AIR CONTAMINANTS (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
- I. ALDEHYDES (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
- J. TOTAL REDUCED SULFUR COMPOUNDS (FUEL ONLY)
- K. NITROGEN AND CARBON DIOXIDE
- L. BTU CONTENTS (FUEL ONLY)
- M. POWER OUTPUT

[RULE 1303(b) (1) AND 1303(b) (2) - MODELING AND EMISSION OFFSET], [RULE 1110.2], [RULE 404]

RECORDS SHALL BE KEPT AND MAINTAINED TO PROVE COMPLIANCE WITH ALL CONDITIONS FOR THIS PERMIT. THE RECORDS SHALL BE KEPT ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.

[RULE 204]

### **Emissions And Requirements:**

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 1110.2

NOx: 45.4 PPMV, RULE 1110.2 (WITH ECF ADJUSTMENT FACTOR = 1.26)

ROG: 315 PPMV, RULE 1110.2 (WITH ECF ADJUSTMENT FACTOR = 1.26)

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS SO2: 500 PPMV AS SO2, ORANGE COUNTY, RULE 53



## SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT 21865 Copley Drive, Diamond Bar, CA 91765

Section D Page 58 Facility I.D.#: 029110 Revision #: 01

Date: May 28, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

### PERMIT TO OPERATE

Permit No. G2966 A/N 480912

### **Equipment Description:**

RESOURCE RECOVERY SYSTEM NO. 4 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG4-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, BRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### **Conditions:**

- OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

  [RULE 204]
- 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
  [RULE 204]
- 3. THIS EQUIPMENT SHALL BE OPERATED BY PERSONNEL PROPERLY TRAINED IN ITS OPERATION. [RULE 204]
- 4. THIS ENGINE SHALL HAVE AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER TO DETERMINE THE ENGINE ELAPSED OPERATING TIME FOR EACH FUEL BLEND BURNED.
  [RULE 1110.2]
- 5. A FLOW INDICATING AND RECORDING DEVICE SHALL BE INSTALLED IN THE FUEL GAS, OR FUEL BLEND, SUPPLY LINE TO THE ENGINE TO MEASURE AND RECORD THE QUANTITY OF EACH FUEL GAS (IN SCFM) BURNED.

  [RULE 204]
- 6. SAMPLING PORT SHALL BE INSTALLED FOR THE INLET GAS LINE TO THE ENGINE TO ALLOW THE COLLECTION OF A FUEL GAS OR FUEL BLEND SAMPLES.

  [RULE 204]
- 7. MONTHLY READINGS OF THE BTU CONTENT OF FUEL GAS (BTU/SCF) AT THE COMBINED INLET TO THE CGS ENGINES SHALL BE TAKEN USING AN INSTRUMENT APPROVED BY THE SCAQMD. ALL RESULTS SHALL BE RECORDED.

  [RULE 204]
- 8. ALL RECORDING DEVICES SHALL BE SYNCHRONIZED WITH RESPECT TO THE TIME OF THE DAY. [RULE 204]

Facility I.D.#: 029110 Revision #: 01 DRAFT

Date: April 14, 2009

## **FACILITY PERMIT TO OPERATE** ORANGE COUNTY SANITATION DISTRICT

### PERMIT TO OPERATE

Permit No. TBD A/N 480911

### **Equipment Description:**

RESOURCE RECOVERY SYSTEM NO. 3 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG3-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

#### Conditions:

- 1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW. [RULE 204]
- 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES. [RULE 204]
- 3. THIS EQUIPMENT SHALL BE OPERATED BY PERSONNEL PROPERLY TRAINED IN ITS OPERATION. [RULE 204]
- 4. THIS ENGINE SHALL HAVE AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER TO DETERMINE THE ENGINE ELAPSED OPERATING TIME FOR EACH FUEL BLEND BURNED. [RULE 1110.2]
- 5. A FLOW INDICATING AND RECORDING DEVICE SHALL BE INSTALLED IN THE FUEL GAS, OR FUEL BLEND, SUPPLY LINE TO THE ENGINE TO MEASURE AND RECORD THE QUANTITY OF EACH FUEL GAS (IN SCFM) BURNED. [RULE 204]
- SAMPLING PORT SHALL BE INSTALLED FOR THE INLET GAS LINE TO THE ENGINE TO ALLOW THE COLLECTION OF A FUEL GAS OR FUEL BLEND SAMPLES. [RULE 204]
- MONTHLY READINGS OF THE BTU CONTENT OF FUEL GAS (BTU/SCF) AT THE COMBINED INLET TO THE CGS ENGINES SHALL BE TAKEN USING AN INSTRUMENT APPROVED BY THE SCAQMD. ALL RESULTS SHALL BE RECORDED. [RULE 204]
- 8. ALL RECORDING DEVICES SHALL BE SYNCHRONIZED WITH RESPECT TO THE TIME OF THE DAY. [RULE 204].

Section D Page 72 Facility I.D.#: 029110 Revision #: 01 DRAFT Date: April 14, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

- 9. THE TOTAL HEAT INPUT OF GASEOUS FUEL, OR FUEL BLEND, BURNED IN THIS ENGINE SHALL NOT EXCEED 33 MM BTU PER HOUR. A LOG SHALL BE KEPT INDICATING THE TOTAL HEATING VALUE OF FUEL GAS, OR FUEL BLEND, BURNED IN THIS ENGINE BASED ON THE RECORDED FLOW RATE (SCFM) AND THE LATEST MONTHLY BTU CONTENT READING. [RULE 1303 (b) (1) AND 1303 (b) (2)-MODELING AND EMISSIONS OFFSET]
- 10. THIS EQUIPMENT SHALL BE OPERATED IN COMPLIANCE WITH RULES 218, 431.1 AND 1110.2. [RULE 218, 431.1 AND 1110.2]
- 11. THIS EQUIPMENT SHALL BE OPERATED IN SUCH A MANNER THAT THE FOLLOWING EMISSION RATES ARE NOT EXCEEDED.

AIR CONTAMINANT

CARBON MONOXIDE 600 PPMV AT 15% O2 PARTICULATES (PM10) 0.0058 GRAINS/ DSCF ROG OR TNMHC (AS CARBON) 93 PPMV AT 15% O2

[RULE 1303 (a) (1), 1303(b) (1) AND 1303 (b) (2)-BACT, MODELING AND EMISSIONS OFFSET]

12. THE COMBINED EMISSIONS FROM THE THREE (3) CGS ENGINES, USING CALENDAR MONTHLY EMISSIONS DIVIDED BY 30, SHALL NOT EXCEED THE FOLLOWING:

AIR CONTAMINANT	LBS/DA
CARBON MONOXIDE	2,644
NITROGEN OXIDES (AS NO2)	828
PARTICULATES (PM10)	72
ROG OR TNMHC (AS CH4)	372
SULFUR DIOXIDE	84
[RULE 1303 (b) (2)-EMISSIONS OFFSET]	

- 13. THE OPERATOR SHALL INSTALL AND MAINTAIN A CONTINUOUS EMISSION MONITORING SYSTEM (CEMS), OR AN ALTERNATIVE SYSTEM, AS APPROVED BY THE EXECUTIVE OFFICER, TO MEASURE THE ENGINE EXHAUST FOR NOx AND O2 CONCENTRATIONS ON A DRY BASIS, EXCEPT DURING SHUTDOWN FOR MAINTENANCE OF THE SYSTEM. IN ADDITION, THE CEMS SHALL CONVERT THE ACTUAL NOx TO MASS EMISSION RATES; AND RECORD THE ACTUAL AND CORRECTED ENGINE NOx CONCENTRATION AT 15% O2 AND MASS EMISSION RATES ON AN HOURLY AND DAILY BASIS.

  [RULE 218, RULE 1110.2]
- 14. THE OPERATOR SHALL CONDUCT PERFORMANCE TESTS ANNUALLY. WRITTEN NOTICE OF THE PERFORMANCE TEST SHALL BE PROVIDED TO THE AQMD AT LEAST 7 DAYS PRIOR TO THE TEST SO THAT AN OBSERVER MAY BE PRESENT. A COMPLETE FINAL REPORT OF THE TEST (LBS/HR, PPMVD AT 15% O2, LBS/MMBTU, ETC.) SHALL BE PROVIDED TO THE AQMD WITHIN 45 DAYS AFTER TESTING. ALL TEST RUNS REQUIRED BY AQMD SHALL BE REPORTED. THE TESTS SHALL INCLUDE BUT NOT BE LIMITED TO, A TEST OF THE FUELS BURNED AND ENGINE EXHAUST FOR:
  - A. TOTAL NON-METHANE HYDROCARBONS (EXHAUST ONLY)
  - B. CARBON MONOXIDE (EXHAUST ONLY)
  - C. TOTAL PARTICULATE MATTER (EXHAUST ONLY).

Section D Page 73 Facility I.D.#: 029110 Revision #: 01 DRAFT Date: April 14, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

- D. OXIDES OF NITROGEN (EXHAUST ONLY).
- E. OXYGEN
- F. FLOW RATE
- G. MOISTURE
- H. TOXIC AIR CONTAMINANTS (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
- I. ALDEHYDES (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
- J. TOTAL REDUCED SULFUR COMPOUNDS (FUEL ONLY)
- K. NITROGEN AND CARBON DIOXIDE
- L. BTU CONTENTS (FUEL ONLY)
- M. POWER OUTPUT

[RULE 1303(b) (1) AND 1303(b) (2) - MODELING AND EMISSION OFFSET], [RULE 1110.2], [RULE 404]

15 RECORDS SHALL BE KEPT AND MAINTAINED TO PROVE COMPLIANCE WITH ALL CONDITIONS FOR THIS PERMIT. THE RECORDS SHALL BE KEPT ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.
[RULE 204]

### **Emissions And Requirements:**

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 1110.2

NOx: 45.4 PPMV, RULE 1110.2 (WITH ECF ADJUSTMENT FACTOR = 1.26)

ROG: 315 PPMV, RULE 1110.2 (WITH ECF ADJUSTMENT FACTOR = 1.26)

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

# SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT ENGINEERING AND COMPLIANCE DIVISION PERMIT APPLICATION EVALUATION AND CALCULATIONS PROCESSED BY GCR PAGE 6 1 APPL NO SEE BELOW 4/14/2009 PROCESSED BY GCR COMP

### PERMIT TO OPERATE (CHANGE OF CONDITION) EVALUATION

**APPLICANT'S NAME:** 

ORANGE COUNTY SANITATION DISTRICT (OCSD)

**MAILING ADDRESS:** 

10844 ELLIS AVENUE

FOUNTAIN VALLEY, CA 92708

ATTN.: VLAD KOGAN, SENIOR SCIENTIST

**EQUIPMENT ADDRESS:** 

22212 BROOKHURST STREET

(WASTEWATER TREATMENT PLANT NO. 2) HUNTINGTON BEACH, CA 92646-8406

FACILITY ID NO.:

029110

### **EQUIPMENT DESCRIPTION:**

### **APPLICATION NO. 480908**

RESOURCE RECOVERY SYSTEM NO. 1 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG1-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### **APPLICATION NO. 480909**

RESOURCE RECOVERY SYSTEM NO. 2 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG2-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### APPLICATION NO. 480911

RESOURCE RECOVERY SYSTEM NO. 3 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG3-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT	PAGES	PAGE
	6	2
ENGINEERING AND COMPLIANCE DIVISION	APPL NO	DATE
	SEE BELOW	4/14/2009
PERMIT APPLICATION EVALUATION AND CALCULATIONS	PROCESSED BY	CHECKED BY
Land to the state of the state	GCR	

### **APPLICATION NO. 480912**

RESOURCE RECOVERY SYSTEM NO. 4 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG4-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### **APPLICATION NO. 480916**

RESOURCE RECOVERY SYSTEM NO. 5 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG5-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

Conditions: (A/N 480908, 480909, 480911, 480912 and 480916)

- 1. OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.
  [RULE 204]
- 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TIMES.
  [RULE 204]
- 3. THIS EQUIPMENT SHALL BE OPERATED BY PERSONNEL PROPERLY TRAINED IN ITS OPERATION.
  [RULE 204]
- 4. THIS ENGINE SHALL HAVE AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER TO DETERMINE THE ENGINE ELAPSED OPERATING TIME FOR EACH FUEL BLEND BURNED.

  [RULE 1110.2]
- 5. A FLOW INDICATING AND RECORDING DEVICE SHALL BE INSTALLED IN THE FUEL GAS, OR FUEL BLEND, SUPPLY LINE TO THE ENGINE TO MEASURE AND RECORD THE QUANTITY OF EACH FUEL GAS (IN SCFM) BURNED.
  [RULE 204]
- 6. SAMPLING PORT SHALL BE INSTALLED FOR THE INLET GAS LINE TO THE ENGINE TO ALLOW THE COLLECTION OF A FUEL GAS OR FUEL BLEND SAMPLES.
  [RULE 204]

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT	PAGES	PAGE
	6	3.
ENGINEERING AND COMPLIANCE DIVISION	APPL NO	DATE
	SEE BELOW	4/14/2009
PERMIT APPLICATION EVALUATION AND CALCULATIONS	PROCESSED BY	CHECKED BY
The state of the s	GCR	6

- 7. MONTHLY READINGS OF THE BTU CONTENT OF FUEL GAS (BTU/SCF) AT THE COMBINED INLET TO THE CGS ENGINES SHALL BE TAKEN USING AN INSTRUMENT APPROVED BY THE SCAQMD. ALL RESULTS SHALL BE RECORDED.

  [RULE 204]
- 8. ALL RECORDING DEVICES SHALL BE SYNCHRONIZED WITH RESPECT TO THE TIME OF THE DAY.
  [RULE 204]
- 9. THE TOTAL HEAT INPUT OF GASEOUS FUEL, OR FUEL BLEND, BURNED IN THIS ENGINE SHALL NOT EXCEED 33 MM BTU PER HOUR. A LOG SHALL BE KEPT INDICATING THE TOTAL HEATING VALUE OF FUEL GAS, OR FUEL BLEND, BURNED IN THIS ENGINE BASED ON THE RECORDED FLOW RATE (SCFM) AND THE LATEST MONTHLY BTU CONTENT READING.

  [RULE 1303 (b) (1) AND 1303 (b) (2)-MODELING AND EMISSIONS OFFSET]
- 10. THIS EQUIPMENT SHALL BE OPERATED IN COMPLIANCE WITH RULES 218, 431.1 AND 1110.2.
  [RULE 218, 431.1 AND 1110.2]
- 11. THIS EQUIPMENT SHALL BE OPERATED IN SUCH A MANNER THAT THE FOLLOWING EMISSION RATES ARE NOT EXCEED.

AIR CONTAMINANT

CARBON MONOXIDE 600 PPMV AT 15% O2 PARTICULATES (PM10) 0.0058 GRAINS/ DSCF ROG OR TNMHC (AS CARBON) 93 PPMV AT 15% O2

[RULE 1303 (a) (1), 1303(b) (1) AND 1303 (b) (2)-BACT, MODELING AND EMISSIONS OFFSET]

12. THE COMBINED EMISSIONS FROM THE THREE (3) CGS ENGINES, USING CALENDAR MONTHLY EMISSIONS DIVIDED BY 30, SHALL NOT EXCEED THE FOLLOWING:

AIR CONTAMINANT	LBS/DAY
CARBON MONOXIDE	2,644
NITROGEN OXIDES (AS NO2)	828
PARTICULATES (PM10)	72
ROG OR TNMHC (AS CH4)	372
SULFUR DIOXIDE	84
[RULE 1303 (b) (2)-EMISSIONS OFFSET]	

SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT	PAGES	PAGE
	6	4
ENGINEERING AND COMPLIANCE DIVISION	APPL NO	DATE
	SEE BELOW	4/14/2009
PERMIT APPLICATION EVALUATION AND CALCULATIONS	PROCESSED BY	CHECKED BY
	GCR	

- 13. THE OPERATOR SHALL INSTALL AND MAINTAIN A CONTINUOUS EMISSION MONITORING SYSTEM (CEMS), OR AN ALTERNATIVE SYSTEM, AS APPROVED BY THE EXECUTIVE OFFICER, TO MEASURE THE ENGINE EXHAUST FOR NOX AND OZ CONCENTRATIONS ON A DRY BASIS, EXCEPT DURING SHUTDOWN FOR MAINTENANCE OF THE SYSTEM. IN ADDITION, THE CEMS SHALL CONVERT THE ACTUAL NOX TO MASS EMISSION RATES; AND RECORD THE ACTUAL AND CORRECTED ENGINE NOX CONCENTRATION AT 15% OZ AND MASS EMISSION RATES ON AN HOURLY AND DAILY BASIS.

  [RULE 218, RULE 1110.2]
- 14. THE OPERATOR SHALL CONDUCT PERFORMANCE TESTS ANNUALLY. WRITTEN NOTICE OF THE PERFORMANCE TEST SHALL BE PROVIDED TO THE AQMD AT LEAST 7 DAYS PRIOR TO THE TEST SO THAT AN OBSERVER MAY BE PRESENT. A COMPLETE FINAL REPORT OF THE TEST (LBS/HR, PPMVD AT 15% O2, LBS/MMBTU, ETC.) SHALL BE PROVIDED TO THE AQMD WITHIN 45 DAYS AFTER TESTING. ALL TEST RUNS REQUIRED BY AQMD SHALL BE REPORTED. THE TESTS SHALL INCLUDE BUT NOT BE LIMITED TO, A TEST OF THE FUELS BURNED AND ENGINE EXHAUST FOR:
  - A. TOTAL NON-METHANE HYDROCARBONS (EXHAUST ONLY)
  - B. CARBON MONOXIDE (EXHAUST ONLY)
  - C. TOTAL PARTICULATE MATTER (EXHAUST ONLY).
  - D. OXIDES OF NITROGEN (EXHAUST ONLY).
  - E. OXYGEN
  - F. FLOW RATE
  - G. MOISTURE
  - H. TOXIC AIR CONTAMINANTS (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
  - I. ALDEHYDES (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
  - J. TOTAL REDUCED SULFUR COMPOUNDS (FUEL ONLY)
  - K. NITROGEN AND CARBON DIOXIDE
  - L. BTU CONTENTS (FUEL ONLY)
  - M. POWER OUTPUT

[RULE 1303(b) (1) AND 1303(b) (2) - MODELING AND EMISSION OFFSET], [RULE 1110.2], [RULE 404]

15 RECORDS SHALL BE KEPT AND MAINTAINED TO PROVE COMPLIANCE WITH ALL CONDITIONS FOR THIS PERMIT. THE RECORDS SHALL BE KEPT ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.

[RULE 204]

### **EMISSIONS AND REQUIREMENTS:**

16. THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

CO: 2000 PPMV, RULE 1110.2

NOX: 45.4 PPMV, RULE 1110.2 (WITH 1.26 ECF ADJUSTMENT FACTOR)

ROG: 315 PPMV, RULE 1110.2 (WITH 1.26 ECF ADJUSTMENT FACTOR)

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS

### SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT

### ENGINEERING AND COMPLIANCE DIVISION

### PERMIT APPLICATION EVALUATION AND CALCULATIONS

PAGES	PAGE
6	5
APPL NO	DATE
SEE BELOW	4/14/2009
PROCESSED BY	CHECKED BY
GCR	

### **BACKGROUND:**

On April 4, 2008, the above A/Ns 4890908, 909, 911, 912 & 916 (identical equipment) were submitted by the Orange County sanitation District (OCSD) for change of condition for NOx and VOC emission concentrations, per Rule 1110.2 (d) (1) (C), amended February 1, 2008. For these applications, OCSD has also requested in their submittal letter (March 27, 2008) to allow greater than 10% natural gas usage for these biogas engines. OCSD has proposed to allow up to 25% natural gas. Each identical equipment is part of the Central generation System (CGS), spark-ignited internal combustion engine, located at Huntington Beach, Plant No. 2.

Based on past conversations with OCSD staff, on February 12, 2009, OCSD has informed to process these applications for ECF based concentration limits to expedite permit issuance (see e-mail correspondences of 2/11 and 2/12/09 from OCSD). Therefore, these applications are not evaluated for initial request of >10% NG usage at this time. OCSD was informed to file separate applications, in future, if >10% NG usage is needed for these CGS engines to comply with Rule 1110.2 requirements.

This is a Title V facility and initial Title V facility permit was issued that became effective January 12, 2009. Application for Title V permit revision is submitted.

### **PROCESS DESCRIPTION:**

On 01/12/2009, initial Title V permit was issued.

Title V facility permit contained reissued permits, that superseded previous permits issued on 7/08/2008. The following are the most recent permits granted for the above engines,

R-96019 / A/N 414653 (CG1-HB) R-96020 / A/N 414654 (CG2-HB) R-96021 / A/N 414655 (CG3-HB) R-96022 / A/N 414656 (CG4-HB) R-96023 / A/N 414657 (CG5-HB)

To comply with Rule (d) (1) ( C ), Table III, Emission Correction factor (ECF) based concentrations, OCSD had conducted required source tests [Per R1110.2 (d) (1) ( C ) (i) and (ii)] for each engine during June and July 2008. The tests were conducted by SCEC and Advanced Engine Technologies Corp. (AETC) as required under R1110.2 (ASME Performance Test Code PTC 17-1973) for high, medium and low load, and average values determined for NOx, VOC and ECF (see summary results tables in folder).

Average results from three different loads are summarized below,

CGS Engines	Units	No. 1	No. 2	No. 3	No. 4	No. 5
Exhaust Flow Rate	DSCFM	10,230	9,751	10,634	10,822	9,559
O <sub>2</sub>	%O2	12.21	12.01	12.44	12.47	12.20
NO <sub>x</sub>	ppmvd @ 15% O2	28.2	23.4	22.6	23.6	22.4
TNMOC	ppmvd @ 15% O2	97.5	93.3	34.1 ?	74.3	N/A
CO (for information)	ppmvd @ 15% O2	440.3	420.6	?	514.5	457.3
Measured Qa	Btu/Bhp-hr	7438.3	7403.7	7,403.3	7789.2	6838.7
$ECF = 9250 / Q_a$		1.25	1.26	1.25	1.19	1.37

# SOUTH COAST AIR QUALITY MANAGEMENT DISTRICT ENGINEERING AND COMPLIANCE DIVISION PERMIT APPLICATION EVALUATION AND CALCULATIONS PROCESSED BY GCR PAGE 6 6 6 APPL NO SEE BELOW 4/14/2009 PROCESSED BY GCR

### EMISSION (ppmvd at 15% O2):

For these identical engines, average ECF = 1.26 will be used to determine ECF based emission (con.)

$$NO_x = 36 \times 1.26 = 45.4 \text{ ppmvd}$$

**TNMOC** (VOC) = 
$$250 \times 1.26 = 315 \text{ ppmvd}$$

CO concentration limit is kept as before as no ECF adjustment is required..

New Condition No. 11 is added to the existing engines' permits. Revised Condition No. 12.

Mass emissions are kept same as under previous permit(s);

CO = 27.6 lbs/hr

NOx = 8.52 lbs/hr

PM10 = 0.75 lbs/hr

ROG = 3.87 lbs/hr

SOx = 0.87 lbs/hr

### **RULES EVALUATION:**

Compliance with all applicable rules and regulations is expected. NOx and VOC concentration limits, based on ECF, are imposed, Condition No. 11, per Rule 1110.2 (d) (1) ( C ).

### **RECOMMENDATION**:

Permit to operate for the proposed change of condition for each engine is recommended with above listed conditions.

### Gaurang Rawal

From:

Gaurang Rawal

Sent:

Thursday, February 12, 2009 3:36 PM

To:

Kogan, Vlad

Cc:

Ahn, Terry

Subject: RE: Plant 2 CGS

### Vlad.

This is to confirm my understanding, based on our previous conversations, that the Plant 2 applications for change of condition is for ECF only and will be processed accordingly. Therefore, initial request for >10% natural gas usage for the CGS engines is not evaluated. Any future requirements for >10% natural gas usage under Rule 1110.2 shall be addressed in separate applications.

### Regards,

Gaurang Rawal Air Quality Engineer iery & Waste Management South Coast A.Q.M. D. 21865 Copley Drive Diamond Bar, CA 91765 grawal@agmd.gov Ph: (909) 396-2543 FAX: (909) 396-3341

> ----Original Message----From: Kogan, Vlad

Sent: Thursday, February 12, 2009 2:45 PM

To: Gaurang Rawal Cc: Ahn, Terry

Subject: FW: Plant 2 CGS

### Gaurang,

This e-mail is to confirm our telephone conversation today. Please proceed with our request to include ECF in the permits for Plant 2 CGS engines. The corresponding Title V request for the minor permit revision will be submitted to you shortly. Please contact me or Terry if you have questions. Thanks, VK

From: Kogan, Vladimir

Sent: Wednesday, February 11, 2009 1:44 PM

To: Gaurang Rawal Subject: FW: Plant 2CGS

### Hi Gaurang,

Based on the response I received from our CGS operating people we might agree on the temporary removal of the request to increase natural gas ratio in Plant 2 fuel blend from 10 to 25% as soon as our request to include ECF in our CGS emission limits containing in the same application is processed without further delays. We reserve the right to continue with our request to increase the natural gas concentration as stated in the R1110.

Please contact me if you have questions. Thanks, VK

From: Halverson, David (O&M)

Sent: Thursday, February 05, 2009 11:19 AM

To: Kogan, Vladimir; Thompson, Rob; Van Voorst, Don

**Cc:** Ahn, Terry; Rothbart, Lisa **Subject:** RE: Plant 2CGS

Don and his staff have succeeded in creating procedures to limit the natural gas use and have been successful for the last couple of months in keeping it below 10%. There will be some increased testing associated with the CEMS replacement project but I assume that natural gas usage is not counted toward the 100% limit.

We are OK with removing this exception request for natural gas usage.

Dave

Section D Page 28
Facility LD.#: 029110
Revision-#:-0
Date: January 12, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

### PERMIT TO OPERATE

Existing Po

Permit No. R-F96021 A/N 414655

### **Equipment Description:**

RESOURCE RECOVERY SYSTEM NO. 3 CONSISTING OF:

INTERNAL COMBUSTION ENGINE (CG3-HB), COOPER BESSMER, SPARK IGNITION, FOUR STROKE, WITH A MODIFIED TURBOCHARGED-INTERCOOLED V-16 TYPE, MODEL NO. LSVB-16-SGC, 4166 HP, NATURAL GAS AND/OR DIGESTER GAS FIRED, DRIVING A 3000 KW ELECTRIC GENERATOR, WITH AN EXHAUST HEAT RECOVERY STEAM GENERATOR, 6,010,200 BTU/HR CAPACITY, UNFIRED.

### Conditions:

- OPERATION OF THIS EQUIPMENT SHALL BE CONDUCTED IN ACCORDANCE WITH ALL DATA AND SPECIFICATIONS SUBMITTED WITH THE APPLICATION UNDER WHICH THIS PERMIT IS ISSUED UNLESS OTHERWISE NOTED BELOW.

  [RULE 204]
- 2. THIS EQUIPMENT SHALL BE PROPERLY MAINTAINED AND KEPT IN GOOD OPERATING CONDITION AT ALL TINES.
  [RULE 204]
- 3. THIS EQUIPMENT SHALL BE OPERATED BY PERSONNEL PROPERLY TRAINED IN ITS OPERATION.
  [RULE 204]
- 4. THIS ENGINE SHALL HAVE AN OPERATIONAL NON-RESETTABLE TOTALIZING TIME METER TO DETERMINE THE ENGINE ELAPSED OPERATING TIME FOR EACH FUEL BLEND BURNED. [RULE 1110.2]
- 5. A FLOW INDICATING AND RECORDING DEVICE SHALL BE INSTALLED IN THE FUEL GAS, OR FUEL BLEND, SUPPLY LINE TO THE ENGINE TO MEASURE AND RECORD THE QUANTITY OF EACH FUEL GAS (IN SCFM) BURNED.
  [RULE 204]
- 6. SAMPLING PORT SHALL BE INSTALLED FOR THE INLET GAS LINE TO THE ENGINE TO ALLOW THE COLLECTION OF A FUEL GAS OR FUEL BLEND SAMPLES.
  [RULE 204]
- 7. MONTHLY READINGS OF THE BTU CONTENT OF FUEL GAS (BTU/SCF) AT THE COMBINED INLET TO THE CGS ENGINES SHALL BE TAKEN USING AN INSTRUMENT APPROVED BY THE SCAQMD. ALL RESULTS SHALL BE RECORDED.
  [RULE 204]

Section D Page 29 Facility I.D.#: 029110 Revision #: 0

Date: January 12, 2009

## **FACILITY PERMIT TO OPERATE** ORANGE COUNTY SANITATION DISTRICT

- ALL RECORDING DEVICES SHALL BE SYNCHRONIZED WITH RESPECT TO THE TIME OF THE DAY. 8. [RULE 204]
- 9. THE TOTAL HEAT INPUT OF GASEOUS FUEL, OR FUEL BLEND, BURNED IN THIS ENGINE SHALL NOT EXCEED 33 MM BTU PER HOUR. A LOG SHALL BE KEPT INDICATING THE TOTAL HEATING VALUE OF FUEL GAS, OR FUEL BLEND, BURNED IN THIS ENGINE BASED ON THE RECORDED FLOW RATE (SCFM) AND THE LATEST MONTHLY BTU CONTENT READING. [RULE 1303 (b) (1) AND 1303 (b) (2)-MODELING AND EMISSIONS OFFSET]
- 10. THIS EQUIPMENT SHALL BE OPERATED IN COMPLIANCE WITH RULES 218, 431.1 AND 1110.2. [RULE 218, 431.1 AND 1110.2]
- THIS EQUIPMENT SHALL BE OPERATED IN SUCH A MANNER THAT THE FOLLOWING EMISSION 11. RATES ARE NOT EXCEED.

AIR CONTAMINANT

**CARBON MONOXIDE** 600 PPMV AT 15% O2 PARTICULATES (PM10) 0.0058 GRAINS/ DSCF ROG OR TNMHC (AS CARBON) 93 PPMV AT 15% O2 [RULE 1303 (a) (1), 1303(b) (1) AND 1303 (b) (2)-BACT, MODELING AND EMISSIONS OFFSET]

THE COMBINED EMISSIONS FROM THE FIVE (5) CGS ENGINES, USING CALENDAR MONTHLY 12. EMISSIONS DIVIDED BY 30, SHALL NOT EXCEED THE FOLLOWING:

AIR CONTAMINANT	LBS/DAY
CARBON MONOXIDE	2,644
NITROGEN OXIDES (AS NO2)	828
PARTICULATES (PM10)	72
ROG OR TNMHC (AS CH4)	372
SULFUR DIOXIDE	84
[RULE 1303 (b) (2)-EMISSIONS OFFSET]	

13. THE OPERATOR SHALL INSTALL AND MAINTAIN A CONTINUOUS EMISSION MONITORING SYSTEM (CEMS), OR AN ALTERNATIVE SYSTEM, AS APPROVED BY THE EXECUTIVE OFFICER, TO MEASURE THE ENGINE EXHAUST FOR NOx AND O2 CONCENTRATIONS ON A DRY BASIS, EXCEPT DURING SHUTDOWN FOR MAINTENANCE OF THE SYSTEM. IN ADDITION, THE CEMS SHALL CONVERT THE ACTUAL NOx TO MASS EMISSION RATES; AND RECORD THE ACTUAL AND CORRECTED ENGINE NOX CONCENTRATION AT 15% O2 AND MASS EMISSION RATES ON AN HOURLY AND DAILY BASIS. [RULE 218, RULE 1110.2]

Section D Page 30 Facility I.D.#: 029110

Revision #: 0 Date: January 12, 2009

# FACILITY PERMIT TO OPERATE ORANGE COUNTY SANITATION DISTRICT

- 14. THE OPERATOR SHALL CONDUCT PERFORMANCE TESTS ANNUALLY. WRITTEN NOTICE OF THE PERFORMANCE TEST SHALL BE PROVIDED TO THE AQMD AT LEAST 7 DAYS PRIOR TO THE TEST SO THAT AN OBSERVER MAY BE PRESENT. A COMPLETE FINAL REPORT OF THE TEST (LBS/HR, PPMVD AT 15% O2, LBS/MMBTU, ETC.) SHALL BE PROVIDED TO THE AQMD WITHIN 45 DAYS AFTER TESTING. ALL TEST RUNS REQUIRED BY AQMD SHALL BE REPORTED. THE TESTS SHALL INCLUDE BUT NOT BE LIMITED TO, A TEST OF THE FUELS BURNED AND ENGINE EXHAUST FOR:
  - A. TOTAL NON-METHANE HYDROCARBONS
  - B. CARBON MONOXIDE (EXHAUST ONLY)
  - C. TOTAL PARTICULATE MATTER (EXHAUST ONLY).
  - D. OXIDES OF NITROGEN (EXHAUST ONLY).
  - E. OXYGEN
  - F. FLOW RATE
  - G. MOISTURE
  - H. TOXIC AIR CONTAMINANTS, FOR ONE ENGINE PER YEAR
  - I. ALDEHYDES (EXHAUST ONLY), FOR ONE ENGINE PER YEAR
  - J. TOTAL REDUCED SULFUR COMPOUNDS (INLET)
  - K. NITROGEN AND CARBON DIOXIDE
  - L. BTU CONTENTS (INLET)
  - M. POWER OUTPUT.

[RULE 1303(b) (1) AND 1303(b) (2) - MODELING AND EMISSION OFFSET], [RULE 1110.2], [RULE 404]

15 RECORDS SHALL BE KEPT AND MAINTAINED TO PROVE COMPLIANCE WITH ALL CONDITIONS FOR THIS PERMIT. THE RECORDS SHALL BE KEPT ON FILE FOR AT LEAST FIVE YEARS AND SHALL BE MADE AVAILABLE TO AQMD PERSONNEL UPON REQUEST.

[RULE 204]

### THIS PERMIT TO OPERATE R-F96021 SUPERSEDES PERMIT TO OPERATE F96021 ISSUED 7/07/2008.

### **Emissions And Requirements:**

THIS EQUIPMENT IS SUBJECT TO THE APPLICABLE REQUIREMENTS OF THE FOLLOWING RULES AND REGULATIONS:

16. CO: 2000 PPMV, RULE 1110.2

ROG: 250 PPMV, RULE 1110.2 NOx: 36 PPMV, RULE 1110.2

PM: RULE 404, SEE APPENDIX B FOR EMISSION LIMITS SO2: 500 PPMV AS SO2, ORANGE COUNTY, RULE 53

### **Gaurang Rawal**

From: Kogan, Vlad

Sent: Monday, January 19, 2009 3:20 PM

To: Gaurang Rawal

Subject: FW: Engines Source testing. Facilities ID 017301 abd 029110.

Hi Gaurang,

Maybe it is just a miscommunication but I believe that you have already seen our ECF results and the corresponding testing information. Just in case4 I'm forwarding you it once more.

The testing was conducted by the well-known company – SCEC from Orange, CA (Mike Bell – 714-282-8240). They are working at the majority of our source testing. I believe that Charlie is familiar with the company and its work. They are accredited by SCAQMD.

The ECF part of the testing was run by also very well-known company AETC (Advanced Engine Technologies Corp.) San Leandro, CA. they are supreme authorities on this issue. Their president Greg Beshouri (510-614-6340) – is also well-known to everybody in the engines business.

Please contact me if other information is required.

Do we still need to submit a Title V minor permit revision application?

Thanks, VK

From: Kogan, Vladimir

**Sent:** Thursday, July 31, 2008 3:33 PM

To: 'Charles Tupac'

Cc: 'ADejbahsh@aqmd.gov'; Gaurang Rawal

Subject: Engines Source testing. Facilities ID 017301 abd 029110.

[ r Mr. Tupac,

Enclosed please find the results of source testing of the Orange County Sanitation District (OCSD) Central Power Generator Systems (CGS) Internal Combustion Engines (ICE). Plant No.1 (ID No. 017301) is located in Fountain Valley CA and operates three ICE (A/N 414648, 414649, 414651). Plant No. 2 is located in Huntington Beach, CA (ID No. 029110) and operates five ICE (A/N 414653 to 414657). The testing was conducted in accordance with the requirements of paragraph (f)(1)(C) SCAQMD Rule 1110.2. Full source testing reports are located in this office and will be submitted to you upon request. Please note that that the enclosed source testing was not conducted to comply with the requirements of permits to operate for the engines. The results of the compliance source testing will be submitted to you separately.

Enclosed also are the results of testing and calculation of the Efficiency Correction Factors (ECF) for these engines. The determination of the ECFs is required by the paragraph (d)(1)(C) of the Rule 1110.2. The applications for incorporation of the ECFs in the permit conditions together with the applicable fees were submitted to SCAQMD on March 30, 2008 (Plant 2) and on July 30, 2008 (Plant 1).

If you have questions or further information is required please contact me at 714-593-7085 (vkogan@OCSD.com).

Regards,

VK

### **Gaurang Rawal**

From: Kogan, Vlad

Sent: Tuesday, January 13, 2009 5:19 PM

To: Gaurang Rawal Subject: FW: CGS issues

### Gaurang,

I'm sorry, but it is absolutely necessary for us to receive a positive response to my e-mail from 1/6/09. As You know, we are Title V facility right now and should report any non-compliance. Our engines often operate at 40+ ppm of NOx that is OK with the ECF (e.g. 36 ppm x 1.3=46.8). But without approved ECFs that we submitted back in July 2007 we are not sure that such calculations can be used. Still, we do not have other choice than continue operating the engines under the assumption that our ECFs are confirmed per Rule 1110.2.

The issue of operating at more than 10% natural gas is less burning at the current mode. Still, when flares were monthly tested we didn't have enough di-gas at Plant 2 and were forced to operate engines at more than 10% natural graph lt will happen once every 1.5 months or so. Other possibilities of violating this R1110.2 provisions are also might happen.

So we really need your response asap and even faster. If you think that Charlie/Amir should be involved, please let me know (or transfer this e-mail to them)

Please contact me if you have questions. Thanks,

٧K

**From:** Kogan, Vladimir

Sent: Tuesday, January 06, 2009 2:41 PM

To: Gaurang Rawal

Cc: Ahn, Terry; Rothbart, Lisa

Subject: CGS issues

## Gaurang,

What is a situation with our application for including ECF to our engines emissions data? We submitted the application with the testing result back in July 2008. Can we use these results for calculation the compliance with NOx emission limits (e.g. consider these limits at 43-45 ppm and not at 36 ppm)? Another issue is a permission to run the engines at more than 10% of di-gas. We submitted the application as specified by the Rule 1110.2 almost a year ago. As you understand, we are running engines at almost 100% di-gas but during the flares testing we might not be able to run the engines at 100% di-gas for a short time. In both examples such events are very rare and short-time but being a Title V facilities we'd like to avoid such situations completely. Thanks,

Vlad Kogan Senior Scientist Environmental Compliance Division Orange County Sanitation District

Tel: 714-593-7085 Fax: 714-962-8379

TABLE 1.3
SUMMARY OF RESULTS SCAQMD RULE 1110.2 PTC 17 & 8760 HOUR TEST
OCSD PLANT 2

ENGINE #3-July 10, 2008

	Ju	ly 10, 2008				
Parameter	Units	High Load	Medium Load	Low Load	Average	
NO <sub>x</sub>	ppmvd	35.6	33.7	27.8	32.4	
\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	ppmvd @ 15% O <sub>2</sub>	24.7	23.5	19.5	22.6	
	lb/hr	2.99	2.69	1.91	2,53	
	lb/day	71.7	64.7	45.8	60.7	
со	ppmvd	19.9	19.1	15.2	18.1	9
	ppmvd @ 15% O <sub>2</sub>	13.8	13.3	10.7	12.6	
	lb/hr	1.01	0.93	0.64	0.86	
	lb/day	24.3	22.3	15.2	20.6	1
TGNMEO (1)	ppmvd	-	49.0	-	49.0	
10	ppmvd @ 15% O <sub>2</sub>	<u> </u>	34.1	-	34.1	- 7
	lb/hr	_	1.02	-	1.02	
	lb/day	-	24.5	-	24.5	
$O_2$	%	12.40	12.42	12.48	12.44	
CO <sub>2</sub>	%	7.24	7.25	7.24	7.24	
Measured Q <sub>a</sub>	BTU/BHP-HR	7,048	7,375	7,787	7,403.3	
ECF	-	1.312	(.254)	1.188	1.252	
Load	κw	2,859.0	2,591.0	2,091.0	2,513.7	
	%	95.3	86.4	69.7	83.8	
Volume Flow Rate	DSCFM	11,507	10,967	9,430	10,634	

<sup>(1)</sup> One Method 25.1 Tray (duplicate samples) was collected at average load. Results are the average of both samples.

OCSD Perfori	mance Te	est Sumn	nary	
	Data Re			
		7/10/08	7/10/08	
LSVB16 Unit	3	. ,	, ,	
Time	17:10	18:01	19:07	Average
Generator Data				
	1	2	3	
Amps A:	122	163	154	
Amps B:	121	160	151	
Amps C:	121	160	150	
Voltage (KV):	12.3	12.3	12.2	
Power Factor:	0.80	0.82	0.80	
Factory Generator Efficiency (%):	96.28	96.44		
Power Output (KW):	2091	2859		2514
Power Output (BHP):	2911	3974	3604	3496
rower output (bin ).	2311	3374	2004	3470
Fuel Flow Meter Data				
DI-GAS Fuel Flow (SCFM):	647	782.667	757.67	
NAT-GAS Fuel Flow (SCFM):	10	22	12	
Calc. BSFC(BTU/BHP.Hr):	7787	7048	7375	7403
Calc. BSFC(BTU/KW.Hr):	10841	9796	10260	10299
Emissions Data				
RM NOx:	28.4	34.9	32.9	
RM O2:	12.6%	12.5%		
Calc. RM NOx @15%O2:	20.1	24.5	23.1	22.6
RM CO (ppm):		19.0333	19.033	
RM CO2 (%):	7.13	7.19	7.16	
NOx (lbm/Hr):	1.97	2.96	2.65	2.53
CO (lbm/Hr):	0.64	0.98	0.94	0.85
BSNOx (g/BHP.Hr):	0.31	0.34	0.33	0.33
BSCO (g/BHP.Hr):	0.10	0.11	0.12	0.11
DCNO. (- //W H-).	0.40	0.47	0.46	
BSNOx (g/KW.Hr): BSCO (g/KW.Hr):	0.43	0.47	0.46	0.45
Engine Data	0.14	0.16	0.16	0.15
Speed (RPM):	360	260	260	
AMP ("Hg):	14.1	360	360	
AMT (F):		24.2	20.5	
Load (%):	100.3	103.0	101.7	
• •	69%	95%	85%	
Turbo Speed (RPM): Jacket Water Temp. IN (F):	10470	12983	12171	
, , ,	171	172	170	
Jacket Water Temp. OUT (F):	179	180	178	
Ambient Temp. (F):	74	72	69	
Barometric pressure ("Hg):	30.12	30.12	30.12	
Relative Humidity (%):	68%	73%	80%	
Turbo Air Inlet Temp. (F):	/0.3	78.0333	78	

,

AUTO-RECORDING SUMMARY
OCSD Standard Form

Plant 2 Engine 3 Date #### 7/10/08 7/10/08 Time 17:07 18:06 19:06

Average

3457

### Engine Data

SPEED (rpm):	360.0	360.0	359.9
Torque (%):	0.7	0.9	0.9
Output (bhp):	2851.4	3947.5	3570.7
AMP ("Hg):	14.5	24.2	20.7
PGP (PSI):	21.3	30.6	27.4
PDP (PSI):	14.2	18.7	17.2
AMT (deg F):	100.9	103.5	102.4
IT (deg BTDC):	9.7	9.7	9.7

### Engine Performance

NG Fuel Flow (SCFM):	8.80	24.01	11.36
DG Fuel Flow (SCFM):	651.17	802.20	761.26
LHV Blend Ratio:	98%	95%	98%
BSFC (BTU/BHP-HR):	7983	7286	7469
NOx MASS FLOW (lbm/HR):	1.92	3.07	2.70
CO MASS FLOW (lbm/HR):	0.6	1.0	0.9
BS NOx (g/BHP-HR):	0.305	0.353	0.344
BS CO (g/BHP-HR):	0.10	0.12	0.12

### 7579 2.56 0.87 0.33

0.11

### Emissions Data

RM NOx (ppm):	27.8	35.6	33./
RM O2 (%):	12.5%	12.4%	12.4%
RM NOx @15%O2:	19.5	24.7	23.4
RM CO (ppm):	15	20	19
RM CO @15%O2	10.7	13.8	13.3

22.5

12.6

### Combustion Data

Engine Avg PP (psi):	708	906	840
ngine Avg LOPP (CA deg. ATDC):	15.1	16.4	16.1
Engine Avg Std Dev. PP(psi):	21	27	24
Engine Exhaust Temp.(F):	779	815	804

TABLE 1.4
SUMMARY OF RESULTS SCAQMD RULE 1110.2 PTC 17 & 8760 HOUR TEST

June 18, 2008

,		ne 15, 2005			
Parameter	Units	High Load	Medium Loads	Low Load	Average
$NO_X$	ppmvd	39.6	33.2	28.4	33.8
	ppmvd @ 15% O <sub>2</sub>	27.2	23,2	20.4	23.6
	lb/hr	3.47	2.62	1.98	2.69
	lb/day	83.4	63.0	47.6	64.7
со	ppmvd	655.1	715.3	831.0	733.8
	ppmvd @ 15% O <sub>2</sub>	449.9	498.9	594.7	514.5
	lb/hr	34.94	34.4	35.29	34.88
	lb/day	838.6	825.7	846.9	837.1
TGNMEO (1)	ppmvd	/ -	106.7	-	106.7
	ppmvd @ 15% O <sub>2</sub>	-	74.3	-	74.3
	lb/hr معمر	_	2.19	-	2.19
	lb/day	-	52.5	-	52.5
$O_2$	9%	12.31	12.44	12.66	12.47
CO <sub>2</sub>	%	6.56	6.75	6.34	6.55
Measured Q <sub>a</sub>	BTU/BHP-HR	7,309	7,757	8,302	7,789.2
ECF	-	1.266	(1.193)	1.114	1.191
Load	ĸw	2,974.0	2,467.5	1,988.0	2,476.5
	%	99.1	82.3	66.3	82.6
Volume Flow Rate	DSCFM	12,033	10,852	9,580	10,822

<sup>(1)</sup> One Method 25.3 Tray (duplicate samples) was collected at average load. Due to data scatter results are from fraction 1A.

4/13/08 T/c@ V/Cogun. Page 1 of 2 45.40pm one solution is to amend recently submitted AIN (180911 (CG3-HB), that was for e/c to comply with R1110-2 (7101-NG useage), to include gus pretreation System of Catox, this will require eadlinearl Gaurang Rawal Charles Tupac From: To: Gaurang Rawal

Cc: Amir Dejbakhsh

Subject: RE: Rule 441 Research permit for CG3-HB, AVN 449645, F79473

There was definitely a problem between the time the R441 permit expired and now, but since has recently filed a set of applications, would OCSD prefer to use as a temporary valid permit for existing equipment?

From: Gaurang Rawal

Sent: Wednesday, April 23, 2008 2:51 PM

To: Kogan, Vlad

Cc: Charles Tunac: Amir Defball 1.

Cc: Charles Tupac; Amir Dejbakhsh; Ahn, Terry

Subject: RE: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

Vlad,

Thank you for the prompt reply.

Technically speaking the research permit has expired. As you are aware that the research permit is a temporary permit to investigate initial objectives/goals. As you mentioned that, the equipment life-span is expired and it might be dismantled. I suggest that operations shall be discontinued soon, as CG3-HB will be operating contrary to the recently issued PO F96021 (i.e. equipment description w/o gas pretreatment and catox).

44655

Gaurang Rawal

Air Quality Engineer

Refinery & Waste Management

South Coast A.Q.M. D.

21865 Copley Drive

Diamond Bar, CA 91765

grawal@aqmd.gov

Ph: (909) 396-2543

FAX: (909) 396-3341

----Original Message----

From: Kogan, Vlad

Sent: Wednesday, April 23, 2008 1:15 PM

To: Gaurang Rawal

Cc: Charles Tupac; Amir Dejbakhsh; Ahn, Terry

Subject: RE: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

Gaurang,

You are correct in terms that the catalyst project had been officially completed last summer and the report would be sent to you. But equipment has been functioning so good that we have decided to continue its operating including the extensive monitoring for the time being. Should we apply for the Research permit renewal or act otherwise? It might be dismantled or stop functioning at any time (the manufacturer's life-span had expired long ago) but might continue to operate indefinitely. Your direction or advice on this matter is appreciated.

There are different options under consideration including a possible transfer of the equipment to Plant 1 but so far it is still operating at Plant 2.

Thanks,

From: Gaurang Rawal [mailto:grawal@aqmd.gov]

Sent: Wednesday, April 23, 2008 8:39 AM

To: Kogan, Vladimir

Cc: Charles Tupac; Amir Dejbakhsh

Subject: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

Vlad,

It is our understanding that the Rule 441 research permit for CG3-HB (plant No. 2) for digester gas cleaning system and catalytic oxidizer installations to evaluate the effectiveness for CO reduction and TACs removal (e.g. formaldehyde, acrolein, etc.) has been completed. The research permit was issued November 30, 2005, and an extension was granted until June 30, 2007.

Research permit Condition No. 10 required submittal of the complete report to AQMD with conclusions. We are interested in learning the findings and success of this research study and waiting for the final report. Is OCSD planning such installations at Plant No. 1?

Your attention to his matter and timely submittal of the report is appreciated.

Best Regards,

Gaurang Rawal
Air Quality Engineer
Refinery & Waste Management
South Coast A.Q.M. D.
21865 Copley Drive
Diamond Bar, CA 91765
grawal@aqmd.gov
Ph: (909) 396-2543

FAX: (909) 396-2543

### **Gaurang Rawal**

From: Kogan, Vlad

Sent: Wednesday, April 23, 2008 4:04 PM

To: Gaurang Rawal

Subject: RE: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

### Gaurang,

I understand your e-mail's content. We'll contact the vendor and our people involved and decide what to do with the system. Can we somehow renew or apply for the new research permit? Thanks, VK

If you have some spare time please explain me what is the advantage for the air quality if the system is dismantled and CO emission becomes 95% and toxics emission 70% higher from the engine without it.

VK

F .n: Gaurang Rawal [mailto:grawal@aqmd.gov]

Sent: Wednesday, April 23, 2008 2:51 PM

To: Kogan, Vladimir

Cc: Charles Tupac; Amir Dejbakhsh; Ahn, Terry

Subject: RE: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

Vlad.

Thank you for the prompt reply.

Technically speaking the research permit has expired. As you are aware that the research permit is a temporary permit to investigate initial objectives/goals. As you mentioned that, the equipment life-span is expired and it might be dismantled. I suggest that operations shall be discontinued soon, as CG3-HB will be operating contrary to the recently issued PO F96021 (i.e. equipment description w/o gas pretreatment and catox).

Gaurang Rawal

Cuality Engineer

Connery & Waste Management

South Coast A.Q.M. D.

21865 Copley Drive

Diamond Bar, CA 91765

grawal@aqmd.gov

Ph: (909) 396-2543

FAX: (909) 396-3341

-----Original Message-----From: Kogan, Vlad

Sent: Wednesday, April 23, 2008 1:15 PM

To: Gaurang Rawal

Cc: Charles Tupac; Amir Dejbakhsh; Ahn, Terry

Subject: RE: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

### Gaurang,

You are correct in terms that the catalyst project had been officially completed last summer and the report would be sent to you. But equipment has been functioning so good that we have decided to continue its operating including the extensive monitoring for the time being. Should we apply for the Research permit renewal or act otherwise? It might be dismantled or stop functioning at any time (the manufacturer's life-span had expired long ago) but might continue to operate indefinitely. Your direction or advice on this matter is

appreciated.

There are different options under consideration including a possible transfer of the equipment to Plant 1 but so far it is still operating at Plant 2.

Thanks,

VK

From: Gaurang Rawal [mailto:grawal@aqmd.gov]

Sent: Wednesday, April 23, 2008 8:39 AM

To: Kogan, Vladimir

Cc: Charles Tupac; Amir Deibakhsh

Subject: Rule 441 Research permit for CG3-HB, A/N 449645, F79473

Vlad,

It is our understanding that the Rule 441 research permit for CG3-HB (plant No. 2) for digester gas cleaning system and catalytic oxidizer installations to evaluate the effectiveness for CO reduction and TACs removal (e.g. formaldehyde, acrolein, etc.) has been completed. The research permit was issued November 30, 2005, and an extension was granted until June 30, 2007.

Research permit Condition No. 10 required submittal of the complete report to AQMD with conclusions. We are interested in learning the findings and success of this research study and waiting for the final report. Is OCSD planning such installations at Plant No. 1?

Your attention to his matter and timely submittal of the report is appreciated.

Best Regards,

Gaurang Rawal
Air Quality Engineer
Refinery & Waste Management
South Coast A.Q.M. D.
21865 Copley Drive
Diamond Bar, CA 91765
grawal@aqmd.gov
Ph. (909) 396-2543

Ph: (909) 396-2543 FAX: (909) 396-3341 TERRY AHN
ORANGE COUNTY SANITATION DISTRICT
P O BOX 8127
FOUNTAIN VALLEY, CA 92728

Facility ID: 29110

Located at: 22212 BROOKHURST ST, HUNTINGTON BEACH

Thank you for filing your application(s) with the South Coast Air Quality Management District (AQMD).

The application number(s) assigned by AQMD to your application package(s) is/are on Page 2 of this letter. Please refer to the information on Page 2 when contacting AQMD for assistance. The information you submitted with your application(s) or in your latest submittal is complete to the extent that allows us to begin processing of your application(s), however some clarifying data may still be needed. The acceptance of your application(s) does not imply that permit(s) has/have been approved. The engineer assigned to process your application(s), as indicated below, may contact you if additional information is required.

If you have any question or need additional information about your application(s), please contact the engineer listed below:

**Engineer:** Gaurang Rawal **Telephone:** (909) 396 - 2543

For general information about AQMD's permitting process, please call (909) 396-2468.

cc: Application file(s)

## AQMD PERMIT APPLICATION INFORMATION

## (Please refer to this information when contacting AQMD for Assistance)

4/23/2008

Facility ID: 29110

Application Number (s)	Equipment Description
480908	I C E (>500 HP) NAT & DIGESTER GAS
480909	I C E (>500 HP) NAT & DIGESTER GAS
480911	I C E (>500 HP) NAT & DIGESTER GAS
480912	I C E (>500 HP) NAT & DIGESTER GAS
480916	I C E (>500 HP) NAT & DIGESTER GAS



## ORANGE COUNTY SANITATION DISTRICT

## RECEIVED

108 MAR 27 P4:07

March 25, 2008 SCAOMD EXECUTIVE OFFICE

Dr. Barry Wallerstein Executive Officer South Coast Air Quality Management District 21865 Copley Drive Diamond Bar, CA 91765-4178

Facility ID No. 029110)

From: Office of the Executive Officer To: Markon T	def
cy. EL, Marty C	
3-2-15 . 2 20 for: si	•

phone: (714) 962-2411

fax: (714) 962-0356

www.ocsd.com

mailing address: RO. Box 8127

P.U. Box 8127 Fountain Valley, CA 92728-8127

street address:

10844 Ellis Avenue Fr in Valley, CA 2708-7018

> Member Agencies O

> > Cities

Anaheim Brea Buena Park Cypress Fountain Valley Fullerton Garden Grove Huntington Beach Irvine La Habra La Palma Los Alamitos Namort Beach Orange Placentia Santa Ana Seal Beach Stanton Tustin Villa Park Yorba Linda

County of Orange

Sanitary Districts

Costa Mesa Midway City

Water Districts

Irvine Ranch

The purpose of this letter is to present the Orange County Sanitation District's (OCSD) permit application for a change of conditions to approve the burning of more than 10% natural gas in five digester gas—fueled internal combustion engines, to avoid the flaring of digester gas, operating at our Plant No. 2 Wastewater Treatment Plant located in Huntington Beach, CA. This request is being submitted to you in accordance with the provision of subparagraph (e)(7) of the Rule 1110.2, adopted by SCAQMD's Governing Board on February 1, 2008. With this permit application, we are also requesting a change of conditions for Efficiency Correction Factor (ECF)-corrected emission limits for the engines.

Compliance with SCAQMD Rule 1110.2 for Five Digester Gas-Fueled

Engines at Orange County Sanitation District's Plant No. 2 (SCAQMD)

### **Background Information**

SUBJECT:

The five engines at Plant No. 2, regulated by Rule 1110.2, are part of OCSD's Central Power Generation System (CGS). Each of these engines are rated at 4,166 brake horsepower (hp) and can produce up to 3.0 megawatts (MW) of electricity, thus enabling OCSD to operate its wastewater treatment processes using completely internal sources of power. As an essential public service this increases our ability to reliably provide wastewater treatment to over 2.3 million residents and numerous businesses in Orange County. The engines are fueled mostly by the digester gas produced at Plant No. 2 and supplemented by natural gas on an as needed basis. A minimum of 5% natural gas is required to maintain the pilot light for each engine. We also use a small amount of digester gas on boilers for plant process heat and monthly flaring testing.

In 2007, OCSD produced about 73 million cubic feet (mcf) of digester gas, averaged monthly, as shown in *Table 1 - Plant No. 2, Digester Gas Production, Fuel Consumption and Electricity Generation for 2007.* Based on the high heating value of 620-630 BTU/ft<sup>3</sup> for digester gas and using an energy conversion efficiency factor of 30-33%, this equates to approximately 6.5 to 7.5 MW electricity generated per month. As shown in *Table 2 - Plant No. 2 Power Demands at Different Weather* 



Dr. Barry Wallerstein Page 2 of 3 March 25, 2008

Conditions, the average power demand ranges between 7.8 and 8.5 MW during dry weather period increasing to as high as 16 MW during a severe rainstorm.

In order to avoid flaring and meet the average dry-weather power demand, it is necessary to supplement the digester gas by an average of 22% by heat input of natural gas as shown in Table 1.

### OCSD's Options to Address Rule 1110.2

There are two options available to OCSD to address Rule 1110.2:

Option 1: Operation of Engines at 80% Load and Purchase Power from Southern California Edison (SCE)

Under this option, OCSD would run two engines at about 80% load fueled with 95% digester gas and purchase power from SCE to meet the additional power demand. This would result in flaring of approximately 12 mcf/month of excess digester gas.

Option 2: Purchase Natural Gas to Supplement Digester Gas

Under this option, OCSD would run three engines at an 80% load to consume all of the digester gas produced; and one or more engines would be supplemented with natural gas. This would require approximately 13 mcf/month of natural gas which is between 20-25% of natural gas usage. With this option all digester gas would be utilized and *no flaring* would be required but would subject the engines to the lower emission limits for natural gas-fueled engines. The supplement of natural gas is required to keep the engines in their stable operating range of 80% load. The engine control system cannot regulate the engine speed if operated below a 70% load.

### Conclusion

OCSD's goal is to completely utilize all of its valuable renewable fuel (digester gas) in the operation of its CGS engines while complying with the intent of Rule 1110.2 requirements. Option 2 would best meet that goal.



Dr. Barry Wallerstein Page 3 of 3 March 25, 2008

In summary, in order to avoid flaring digester gas and operate in compliance with Rule 1110.2 OCSD is requesting your approval to use up to 25% natural gas, monthly averaged, in our engines to supplement digester gas usage during normal operations. We would request that the following language in the engines permit conditions (PTC A/N 414653 to 414657) be added after the current Condition 5:

"The Operator may burn more than 10% natural gas when it is necessary if the alternative to limiting natural gas to 10% would be shutting down the engine and flaring more digester gas or the engine requires more natural gas in order to provide enough thermal energy to operate the sewage treatment plant"

We have submitted the engines' operational data including the detailed calculation of Emission Correction Factors to your Permitting staff. The updated data and other pertinent information are attached to this letter. Any other information necessary to process the permit application will be submitted to your staff upon request.

If you have questions or further discussion is required, please contact the undersigned at (714) 593-7080. The staff member assigned to this issue is Dr. Vladimir Kogan and he can be reach at (714) 593-7085.

**Edward Torres** 

Director of Technical Services

ET:wh

H:/dept/ts/620/general data/Air Group/Letters/D1\_VK\_Compliance\_Rule 1110.2 Digester Gas-Fueled P-2\_ID 029110.doc

c: Jay Chen, Senior Air Quality Engineering Manager Charles Tupac, Toxics and Waste Management



### Enclosures:

- Application for changing of permit conditions Form 400-A
- Check for the Applications Processing Fee in the amount of \$8,204.15
- Table 1 Plant No. 2 CGS Energy Output, Digester Gas Production, and Fuel Consumption for 2007
- Table 2 Plant No. 2 Power Demands at Different Weather Conditions